


DETAIL


PRECAST LONGITUDINAL HALF-SECTION

SHOWING POST-TENSIONING CABLE PATHS * MEASURED BEFORE POST-TENSIONING.


** CONTRACTOR MAY ELECT TO CAST THE GIRDER IN ONE PIECE IF THE SHIPPING WEIGHT IS LESS THAN 200 KIPS & THE SHIPPING ROUTE ALLOWS THE SHIPMENT OF LONG GIRDERS.

POST-TENSIONING TABLE





DUCT SPLICE DETAIL



DUCTS

TENDON IN SAG CURVE

STRAND LOCATION DETAIL

& OF

DUCTS

-2" CLR. EXCEPT FOR

SPLAYING AT END

DIAPHRAGMS (TYP.)

-C.G. OF

PROFILE

STRANDS

DIMENSION SHOWN

ON POST-TENSIONING

STRAND PATTERN AT & SPAN

STRAIGHT STRAND LOCATION SEQUENCE SHALL BE AS SHOWN (1) (2) ETC

- 1. THE CAST-IN-PLACE CONCRETE IN DECK SLAB SHALL BE CLASS 4000D. THE MINIMUM COMPRESSIVE STRENGTH OF THE CAST-IN-PLACE CONCRETE AT THE WET JOINT AT THE TIME OF POST-TENSIONING SHALL BE ??? ksi.
- 2. THE MINIUM PRESTRESSING LOAD AFTER SEATING AND THE MINIMUM NUMBER OF PRESTRESSING STRANDS FOR EACH GIRDER SHALL BE AS SHOWN IN POST-TENSIONING TABLE.
- 3. THE DESIGN IS BASED ON ?? INCH DIAMETER LOW RELAXATION STRANDS WITH A JACKING LOAD FOR EACH GIRDER AS SHOWN IN POST-TENSIONING TABLE, AN ANCHOR SET OF % INCH OF CURVATURE FRICTION COEFFICIENT, μ = 0.20 AND A WOBBLE FRICTION COEFFICIENT, k = 0.0002/ft. THE ACTUAL ANCHOR SET USED BY THE CONTRACTOR SHALL BE SPECIFIED IN THE SHOP PLANS AND INCLUDED IN THE TRANSFER FORCE CALCULATIONS.
- 4. THE DESIGN IS BASED ON THE ESTIMATED PRESTRESS LOSS OF POST-TENSIONING STRANDS SHOWN IN POST-TENSIONING TABLE DUE TO STEEL RELAXATION, ELASTIC SHORTENING CREEP AND SHRINKAGE OF CONCRETE.
- 5. THE CONTRACTOR SHALL SUBMIT THE STRESSING SEQUENCE AND ELONGATION CALCULATIONS TO THE ENGINEER FOR APPROVAL. ALL LOSSES DUE TO TENDON VERTICAL AND HORIZONTAL CURVATURE MUST BE INCLUDED IN ELONGATION CALCULATIONS.
 - A. THE PRESTRESSING FORCE SHALL BE DISTRIBUTED WITH AN APPROXIMATELY EQUAL AMOUNT IN EACH WEB.
 - B. NO MORE THAN ONE-HALF OF THE PRESTRESSING FORCE IN ANY WEB MAY BE STRESSED BEFORE AN EQUAL FORCE IS STRESSED IN THE ADJACENT WEBS.
- 6. THE MAXIMUM OUTSIDE DIAMETER OF THE DUCT SHALL BE ??? INCHES. THE AREA OF THE DUCT SHALL BE AT LEAST 2.5 TIMES THE NET AREA OF THE PRESTRESSING STEEL IN THE DUCT.
- 7. ALL TENDONS SHALL BE STRESSED FROM PIER ??.

	Office DE No Office (1),(2) ETC.										
)	ridge Design Engr. M:\STANDARDS\Girders\PT Wide Flange\W95PTG1.MAN										П
4	Supervisor		·			REGION NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS	
,	Designed By										
	Checked By					10	WASH,				
' F	Detailed By					TOP	NUMBER				
	Bridge Projects Engr.					3061	NOMBER				
)	Prelim. Plan By										
	Architect/Specialist	DATE	REVISION	BY	APP'D				'	!	

BRIDGE AND **STRUCTURES** OFFICE



POST-TENSIONING NOTES

STANDARD PRESTRESSED CONCRETE GIRDERS W95PTG SPLICED GIRDER DETAILS 1 OF 5

9

Ø

Tue Jan 09 11:34:18 2007